

|   |   |   |
|---|---|---|
|  | <b>DECLARATION OF PERFORMANCE</b><br><b>N°0022-2013</b><br>amending Annex III to Regulation (EU) No 305/2011 of the European Parliament and of the Council on the model to be used for drawing up a declaration of performance on construction products |  |
|---|---|---|

**1 - Unique identification code of the product-type :**

**PRB CLASSIC F**

**2 - Intended use/es :**

One coat mortar for external use (OC) applicable on walls, ceilings, columns and partitions

**3 - Manufacturer :**

PRB 16 RUE DE LA TOUR 85150 LES ACHARDS

**4 - Authorised representative :**

Non applicable

**5 - System/s of AVCP :**

Systems of assessment 4

**6(a) - Harmonised standard :**

EN998-1 :2016

**Notified body/ies :**

Certificate of conformity of the factory production control N°:

**7- Declared performance/s :**

| Essential characteristics                    | Performances                            |
|--|---|
| Reaction to fire                             | A1                                      |
| Water absorption                             | Wc 2                                    |
| Water vapour permeability                    | $\mu \leq 35$                           |
| Durability (against freeze/thaw)             | –                                       |
| - Water permeability after weathering cycles | $\leq 1 \text{ ml/cm}^2$ after 48 h     |
| - Adhesion after weathering cycles           | 0,2 N/mm <sup>2</sup> - FP: A or B or C |
| Thermal conductivity ( $\lambda_{10}$ , dry) | 0,76 W/mk (Tabulated value)             |
| Dangerous substances                         | See MSDS                                |
|  |   |
|  |   |
|  |   |
|  |   |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

At Achards, on 25/02/2020

Signed for and on behalf of the manufacturer by :

Jacques ESTIVAL  
Directeur technique

