

PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY

LIQUID EPOXY AND PAINT REMOVER (RESIDUES AND STAINS)



PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY
SPECIAL EPOXY CLEANER

The **+**s of PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY

- +** Removes epoxy and paint marks
- +** Improves cleaning after grouting
- +** Does not alter the appearance of joints
- +** General cleaning after grouting and painting

PACKAGING

- 0.250 ml jerry can, box of 6 jerry cans
- 2 litre jerry can.



STORAGE LIFE: 24 months.

CONSUMPTION/USE

For cleaning and stripping, consumption varies depending on the number and type of marks to be removed.

As a guide: 50 to 100 ml/m²

APPLICATIONS

USES

- Indoor and outdoor floors and walls
- Liquid cleaner for removing all traces of epoxy mortar and epoxy, polyurethane* or acrylic* paints or varnishes.
- * Test beforehand.
- Epoxy grouting: dilute with Kitajoint water for a cleaner finish.

SUITABLE SUBSTRATES

- Ceramic tiles, glazed tiles, earthenware, glass tiles*.
- * Porous or sensitive coatings and other materials or coatings: test before use.

Do not apply to decorative materials or paints or decorated tiles that are sensitive to PRB cleaners.

APPLICATION CONDITIONS

- Between 2°C and 35°C.
- To be used on clean, dry surfaces, not exposed to rain or extreme weather conditions or temperatures.

TECHNICAL CHARACTERISTICS

INGREDIENTS

- Colourless alcohol-based solution.

PRODUCT

- Appearance: liquid.
- Odour: light.
- Density: 1.04 (20°C).
- Viscosity: 3000 to 5000 mPa s.
- Leave on for: 10 to 50 mins.

UTILISATION

Please refer to the PRB Process Sheets

PREPARATION

- The surface to be cleaned must be dry and free of dust.

Preliminary test:

We recommend that you test the surface beforehand to ensure that it will not be damaged or stained by the product.

Test a small, hidden area and, after rinsing, check the appearance once the surface has dried.

APPLICATION

Use suitable, solvent-resistant protective gloves (see the EN 374-3 standard: Protective gloves against chemicals and micro-organisms).

For light epoxy/paint marks and residues

- Apply PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY to the surface using a roller or a brush.
- Leave on for at least 10 minutes (50 minutes maximum).
To avoid any risk of injury from slipping, block off the area to be treated.
- Rub the entire surface to be cleaned with a felt pad on the PRB Taloche Finish Époxy finishing trowel until the residue/deposit/mark has disappeared.
- Rinse thoroughly with clean water.

Epoxy grouting:

- After filling the joints, dilute 1 part PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY with 20 parts water, then clean with a finishing felt + sponge trowel.

For thick or thin layers of hardened residue:

- Gently scrape off the epoxy with a plastering spatula or window or paint scraper.
- Finish cleaning with a cloth.
- For stubborn residues, apply a second coat of PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY, wait for it to take effect, then scrub/scrape off the remaining residue.
- Rinse thoroughly with clean water.

Cleaning tools:

- Take a bucket of clean water and add 10% of PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY.
To rub down, use a white felt pad + the PRB Taloche Finish finishing trowel.

Please note: PRB NETTOYANT DÉCAPANT SPÉCIAL ÉPOXY quickly deforms foam sponges.

Painting work (stripping, renovation):
Please contact us.

PRECAUTIONS FOR USE

- To avoid damaging the joints, rinse with water after use.
- Avoid contact or spraying on painted or synthetic surfaces.
- Please read the regulatory packaging label before use.
- **Please read the safety data sheet before use.**
- Wear suitable gloves and protective eyewear.
- In case of contact with skin or eyes, rinse thoroughly with clean water.
- Please read the safety data sheet before disposing of the product (diluted or non-diluted).