

PRB ACCROFIX PÂTE



BONDING COAT PASTE

The **+**s of PRB ACCROFIX PÂTE

- +** Micro-coating for bonding mortars (single-layer, traditional, decorative, etc.) to concrete
- +** Ensures adhesion between the substrate and the finishing render
- +** Easy to use (applied with a roller/brush)
- +** Can be used on new and old substrates

PACKAGING

– 20kg tub.

STORAGE LIFE: 24 months.

CONSUMPTION/USE

0.6 to 0.8 kg/m².

COLOUR: Beige.



Prêt à l'emploi

AREAS OF USE

USES

- Exterior and interior walls.
- Interior walls of houses or buildings.
- Sound, sturdy old builds (please contact us before use).
- French DTU Standards 20.1, 23.1 & 26.1.

SUITABLE SUBSTRATES

- Cast-in-place concretes (French DTU 23.1).
- Cement undercoats and mixes (French DTU 26.1).
- Natural stone.
- For other substrates, please contact us before use.

PROHIBITED SUBSTRATES

- Floors.
- All Gypsum-based substrates (Plaster).
- Paints, thick plastic coatings & textiles.
- Bare wood.
- Horizontal or sloped surfaces (except arches and soffits).

COMPATIBLE COATINGS

- Single-coat and topcoat hydraulic renders.
- Traditional renders.
- Decorative renders.
- Levelling mortars and renders.

APPLICATION CONDITIONS

- Between 5°C and 35°C.
- Do not apply to frozen, thawing, hot or damp surfaces. Do not apply to surfaces in full sunlight or during heavy rain and strong winds.

TECHNICAL CHARACTERISTICS

INGREDIENTS

- Synthetic resins.
- Mineral fillers.
- Specific additives.

PRODUCTS

PASTE:

- Bulk density: 1.7 ± 0.1 t/m³
- pH (alkaline): 8.5 ± 0.5
- Colour appearance: beige

PERFORMANCE WHEN HARDENED:

- Adhesion to concrete: ≥ 0.3 MPa

UTILISATION

SUBSTRATE PREPARATION

- Substrates must be in good condition, adherent, clean and free from residues or other substances that could interfere with adhesion.
- The substrate must not be seeping moisture.
- See "**Substrate preparation**".

APPLICATION

Manual

- Apply using a roller or a brush.
- Clean tools with clean water before the product dries.

DRYING TIME

- From 1 to 24 hrs depending on weather conditions, but not more than 3 days.

PRECAUTIONS FOR USE

- Please read the packaging safety label and safety data sheet before use.