

PRB ACCROFOND I

SOLVENT-BASED INSULATOR AND FIXATIVE PRIMER



The **+**s of PRB ACCROFOND I

- +** Reinforces porous and/or chalky substrates
- +** Improves adhesion for subsequent coatings
- +** Suitable for complex substrates
- +** Fast drying

PACKAGING

– 5-litre metal containers.

STORAGE LIFE: 12 months.

CONSUMPTION/USE

– Approximately 8 to 10 m²/l depending on the porosity of the substrate and the surface finish.

COLOUR: Colourless.



French Standard T 36-005: Category I - Class 7b1

Prêt à l'emploi

AREA OF USE

USES

- PRB ACCROFOND I is used to consolidate and stabilise the surface of interior and exterior walls in new build or renovation projects prior to repainting.

REFERENCE DOCUMENTS

- PRB Technical Data Sheets
- NF DTU standard 59-1

SUITABLE SUBSTRATES

- Concrete.
- Cement mortar.
- Plaster.
- CTB.H & CTB.X wood panels.
- Whitewash.
- Adherent and resistant silicate-based paints and coatings.

For all other substrates: please contact the PRB technical department.

PROHIBITED SUBSTRATES

- Horizontal surfaces or surfaces with a slope of less than 45° exposed to rain.
- Floors.
- Flexible waterproof coatings.

APPLICATION CONDITIONS

- Between 5°C and 35°C.

PRECAUTIONS FOR USE

- Before applying, protect the painted parts of the building and all openings (windows and door frames)...

DURING APPLICATION:

- Make sure the room is well ventilated when applying indoors.
- We strongly recommend wearing safety goggles to avoid contact with your eyes.
- Gloves must be worn when handling the product.
- Tools should always be cleaned with White Spirit before they dry out.
- Thoroughly wipe down all exposed surfaces before closing the container.
- If splashes occur on parts other than those to be treated, wipe off quickly before drying.

TECHNICAL CHARACTERISTICS

INGREDIENTS

- Solvent-based acrylic copolymer resins.
- Specific additives.

PRODUCTS

- Appearance: Satin.
- Solvent: White Spirit.
- Density: 0.85 ± 0.05.
- Flammable product.

UTILISATION

SUBSTRATE PREPARATION

- Substrates must be sound, clean, dry and free from all traces of oil or dust.
- Remove any non-resistant surfaces.
- Carefully brush and vacuum to remove dust.

APPLICATION

Application materials:

- An 18-20 mm woven or textured polyamide roller, depending on the substrate.
- Paintbrush.
- Airless paint sprayer

- PRB ACCROFOND I may need to be re-mixed before use.
- The product is ready to use: do not dilute.

RECOATING

- For use with PRB paints and coatings.
- Dries in 2 to 6 hours, depending on the temperature and porosity of the substrate.

NB: the product must not be left exposed, it must be covered.

CLEANING TOOLS AFTER USE:

- Clean with White Spirit before they dry out.

PRECAUTIONS FOR USE

- Please read the packaging safety label and safety data sheet before use.