

PRB HYDROFUGE



AQUEOUS PHASE WATERPROOFING SOLUTION

CONSTRUCTION MATERIALS

The PRB HYDROFUGE

- Preserves the original appearance of the materials
- Reduces soiling and the growth of micro-organisms
- Coverable

PACKAGING

- 20 l Jerricans.

STORAGE: 12 months.

CONSUMPTION

– minimum 0.20 l/m² for non-porous materials
 – Up to about 0.40 l/m² for porous materials.
 Consumptions may therefore vary depending on the porosity of the treated substrate and the spray gun setting.

COLOUR: clear.



Ready-to-use

AREA OF USE

USE

- Exterior
- Hydraulic binder based renders (conventional or single-coat).
- Concretes.
- Terracotta tiles and tile floorings.
- Stone floor or patio coverings*.
- Hydraulic binder based visible masonry pointing (conventional or single-coat).
- A prior test is recommended.
- For other substrates and uses, contact us.

APPLICATION CONDITIONS

- Between 5°C and 30°C.

Should not be used:

- On wet and/or water impregnated substrates.
- In the presence of frost.
- On frozen or thawing masonry.

Make sure to protect all surfaces near or adjacent to the substrates to be treated (joinery, glazing, shutters, rainwater drainage structures...).

TECHNICAL SPECIFICATIONS

PRODUCTS

- Appearance: liquid.
- Density: < 1 t/m³
- pH (alkaline): 11 ± 0.5

APPLICATION

APPLICATION

- Use the product undiluted on a clean, dry substrate.
- Mix the product before applying it in order to obtain a good consistency.

Application is by complete saturation of the substrate, until the product no longer penetrates:

By spraying: at low pressure (garden sprayer)
 By brushing: brush or long-haired wool roller.

PRECAUTIONS FOR USE

- Read the regulatory labelling on the package and read the safety data sheet before using.
- Wear protective goggles, a mask and protective gloves, as well as work clothing.
- Do not ingest and avoid any contact with food.
- In the event of accidental spraying in the eyes or on the skin, rinse with plenty of clean water.
- In the event of an accident, get medical advice.