

PRB SR ADDITIVE

DRYING ACCELERATOR FOR FINISHING PRODUCTS



The PRB SR ADDITIF

-  Forms a surface film allowing quick drying of TPC, paints and PRB FONDISOL PE
-  Ideal in wet and cold weather

PACKAGING

– Box of 30 plastic 250 ml containers.

STORAGE: 12 months.

CONSUMPTION

– 1 dose of 250 ml for 17 to 25 kg bucket

COLOUR: From clear to slightly yellow.



Ready-to-use

AREA OF USE

USE

- PRB SR ADDITIF is used on interior and exterior walls.

DEFINITION

PRB SR ADDITIF is a liquid additive designed to speed up drying and form a surface film thereby protecting PRB finishes from the rain.

APPLICATION CONDITIONS

- Between 1°C and 15°C.

IT MUST NOT BE USED:

- During frosts, at temperatures below 1°C.
- On frozen or thawing masonry.
- In hot spells in excess of 15°C
- In strong winds (dry or not) or in rain.
- Not suitable for mineral products.

PRECAUTIONS FOR USE

- PRB SR ADDITIF in high doses can cause risks of altering TMC characteristics.

TECHNICAL SPECIFICATIONS

PRODUCTS

- Appearance: liquid.
- Colour: from clear to slightly yellow.
- Density: 1.05 ± 0.05
- pH: 10.5 ± 0.5

APPLICATION

After the addition of PRB SR ADDITIF, it is essential to quickly mix the whole using a mixer at a maximum speed of 300 rpm.