

PRB HYDROFUGE

WATER-BASED SOLUTION FOR WATERPROOFING CONSTRUCTION MATERIALS



The +s of PRB HYDROFUGE

- + Ideal for waterproofing surfaces
- + Powerful waterproofing agent with pearlescent effect
- + Slows urban dirt and grime and development of microorganisms
- + Conserves the original appearance of materials
- + Can be covered with different paints



PACKAGING

– 20l jerrycans.

STORAGE LIFE: 12 months.

CONSUMPTION/USE

Consumption for information purposes depending on type and porosity of substrate to be treated:

- Concrete: 2.5 to 10m²/l
- Renders: 1 to 2.5m²/l
- Terracotta tiles: 1.5 to 5m²/l
- Facing panels: 5 to 20m²/l

COLOUR: transparent after drying.



AREA OF USE

USES

PRB HYDROFUGE effectively waterproofs, protects interior/exterior walls, exterior floors and roofs against humidity, as well as limiting dirt and grime and development of microorganisms, increasing their durability.

- Exterior, interior.
- Hydraulic binder-based renders (traditional or single-coat renders)
- Concrete.
- Terracotta tiles and tiled flooring*.

- Stone floor or patio coverings*.
- Hydraulic binder-based visible masonry joints (traditional or single-coat renders).

*Prior testing recommended.

- For other substrates or uses, please contact us beforehand.

APPLICATION CONDITIONS

- Between 5°C and 30°C.

Not for use:

- On wet and/or water-saturated substrates.
- In case of freezing temperatures, on frozen or thawing substrates.

Take care to protect all surfaces close or next to substrates to be treated (window/door frames, glazing, shutters, rainwater drainage systems, etc.).

TECHNICAL CHARACTERISTICS

PRODUCTS

- Appearance: white milky liquid, colourless after drying.
- Density: approx. 1
- pH : 7.5 ± 0.5

UTILISATION

APPLICATION

- Use the product undiluted on a clean, dry substrate.
- If necessary, clean the substrate beforehand with PRB ACTIFLASH.
- Stir the product before application to obtain good homogeneity.

Apply to maximum substrate saturation, until the product is no longer absorbed:

By spraying: low pressure (garden sprayer)
By painting: brush or long-pile wool roller.

- To optimise the effectiveness of PRB HYDROFUGE, it is advised to apply it to a dry, absorbent substrate, protecting it from rain for at least 12 hours.

PRECAUTIONS FOR USE

- Please read the packaging safety label and safety data sheet before use.
- Wear goggles, a mask and protective gloves, as well as overalls.
- Do not swallow and avoid contact with food.
- In case of accidental splashing in eyes or on skin, rinse with plenty of clean water.
- In case of accident, seek medical assistance.